

Project 25 Compliance Assessment Program
SDOC – L3HARRIS – XL-95P
October 25, 2022

SUBSCRIBER PRODUCT INFORMATION

Subscriber Info	Detail
Model Name:	XL-95P
Tested Software Versions:	XLPR14C07, XLPR12A14, XLPR07B12, XLPR06D03, XLPR05D05, XLPR04B09, XLPR02A28, XGPR01A
Hardware Capabilities/Options & Software Options:	SW Options: P25 Trunking, P25 Phase 2 TDMA, AES-256 Encryption, P25 Data (for Short Message/Status Update/Message Update interoperability tests only) Frequency Bands: 700/800 MHz, UHF, VHF

TEST REQUIREMENTS CAB IDENTIFICATION

This product was tested according to the P25 CAP Test Requirements Compliance Assessment Bulletin (CAB) indicated by the checked box.

check one	P25 CAP Test Requirement CAB	Details
	P25-CAB-CAI_TEST_REQ – July 2017	Includes August 2016 P25 CAP Test Requirements; Adds TDMA performance and interoperability testing and trunked supplementary data testing
X	P25-CAB-CAI_TEST_REQ - October 2018	Includes all July 2017 P25 CAP Test Requirements; Adds minor updates to conventional interoperability testing due to TIA standard update

SUMMARY TEST REPORT IDENTIFIER¹

Summary Test Report (STR) Identifier:	STR-L3HARRIS-SUBSCRIBERS
---------------------------------------	--------------------------

CONTACT INFORMATION

Vendor Info	Details
Vendor Name:	Harris Corporation, Communication Systems, PSPC
Vendor Website URL:	http://www.l3harris.com/all-capabilities/public-safety-and-critical-communications
P25 CAP Contact Name:	David Prather
P25 CAP Contact Phone:	(434) 455-6742
P25 CAP Contact Email:	dprather@harris.com

¹ The Summary Test Report for this product is available upon request. Please send your STR request to P25CAP@hq.dhs.gov and please include the subscriber 'Vendor Name'.

Project 25 Compliance Assessment Program
SDOC – L3HARRIS – XL-95P
October 25, 2022

ENCRYPTION STATEMENT

This product complies with the P25 CAP Encryption Requirements CAB (P25-CAB-ENC_REQ). The checked box indicates how the product was tested.

X	Tested with the AES 256 encryption algorithm and shall be available with AES 256 encryption at a minimum or without any encryption of any type.
	Tested without the AES 256 encryption algorithm and shall only be available without any encryption of any type.

CONVENTIONAL PERFORMANCE

The Subscriber product has been tested for Conventional Performance. All requirements were passed except for those requirements identified below under Unsupported or Failed Requirements.

P25 CAP Conventional Performance Testing Coverage

Receiver Tests: Reference Sensitivity, Faded Reference Sensitivity, Signal Delay Spread Capability, Adjacent Channel Rejection, Offset Adjacent Channel Rejection, Co-Channel Rejection, Spurious Response Rejection, Intermodulation Rejection, Signal Displacement Bandwidth, Late Entry Unsilence Delay, and Receiver Throughput Delay.

Transmitter Tests: Unwanted Emissions (Adjacent Channel Power Ratio), Transmitter Power and Encoder Attack Time, Transmitter Throughput Delay, Frequency Deviation for C4FM, and Modulation Fidelity, Transient Frequency Behavior.

Unsupported or Failed Requirements

1. None.

TRUNKING PERFORMANCE - FDMA

The Subscriber product has been tested for Trunking Performance - FDMA. All requirements were passed except for those requirements identified below under Unsupported or Failed Requirements.

P25 CAP FDMA Trunking Performance Testing Coverage

Receiver Tests: Reference Sensitivity, Faded Reference Sensitivity, Signal Delay Spread Capability, Adjacent Channel Rejection, Offset Adjacent Channel Rejection, Co-Channel Rejection, Spurious Response Rejection, Intermodulation Rejection, and Signal Displacement Bandwidth.

Transmitter Tests: Unwanted Emissions (Adjacent Channel Power Ratio), Power Attack time, Encoder Attack Time, Transmitter Throughput Delay, Frequency Deviation for C4FM, and Modulation Fidelity, Transient Frequency Behavior.

Trunked Tests: Trunking Control Channel Slot Times, Trunking Request Time, and Transmitter Time to Key on a Traffic Channel.

Project 25 Compliance Assessment Program
SDOC – L3HARRIS – XL-95P
October 25, 2022

Unsupported or Failed Requirements

1. 45ms slot times not supported.

TRUNKING PERFORMANCE - TDMA

The Subscriber product has been tested for Trunking Performance - TDMA. All requirements were passed except for those requirements identified below under Unsupported or Failed Requirements.

P25 CAP TDMA Trunking Performance Testing Coverage

Receiver Tests: Reference Sensitivity, Faded Reference Sensitivity, Signal Delay Spread Capability, Adjacent Channel Rejection, Offset Adjacent Channel Rejection, Co-Channel Rejection, Spurious Response Rejection, Intermodulation Rejection, and Signal Displacement Bandwidth.

Transmitter Tests: Unwanted Emissions (Adjacent Channel Power Ratio), Frequency Deviation for H-CPM, Modulation Fidelity, Symbol Rate Accuracy, H-CPM Logical Channel Power measurements, and H-CPM Channel Time Alignment.

Unsupported or Failed Requirements

1. None.

CONVENTIONAL DIRECT MODE INTEROPERABILITY

The Subscriber product has been tested for Conventional Direct Mode Interoperability. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP Direct Mode Interoperability Testing Coverage

Network Access Code (NAC) Operation, Group Voice Call, Emergency Call, Unit-to-Unit Voice Call, Encryption, Call Alert, Radio Check, Message Update, Status Update, Status Query, and Radio Unit Monitor.

Unsupported or Failed Test Cases

1. Call Alert, Radio Check, Message Update, Status Update, Status Query, Radio Unit Monitor are unsupported

Optional Product Capabilities Required to Pass Test Cases

1. In order to pass the supported Encryption test case, a subscriber with the AES-256 Encryption capability is required.

CONVENTIONAL REPEAT MODE INTEROPERABILITY

The Subscriber product has been tested for Conventional Repeat Mode Interoperability. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test

Project 25 Compliance Assessment Program
SDOC – L3HARRIS – XL-95P
October 25, 2022

cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP Repeat Mode Interoperability Testing Coverage

Network Access Code (NAC) Operation, Group Voice Call, Emergency Call, Unit-to-Unit Voice Call, Encryption, Call Alert, Radio Check, Message Update, Status Update, Status Query, and Radio Unit Monitor.

Unsupported or Failed Test Cases

1. Call Alert, Radio Check, Short Message, Status Update, Status Query, Radio Unit Monitor are unsupported.

Optional Product Capabilities Required to Pass Test Cases

1. In order to pass the supported Encryption test case, a subscriber with the AES-256 Encryption capability is required.

CONVENTIONAL REPEAT MODE with DISPATCH MONITORING CONSOLE INTEROPERABILITY

The Subscriber product has been tested for Conventional Repeat Mode with Dispatch Monitoring Console Interoperability. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP Repeat Mode Interoperability Testing Coverage

Group Voice Call, Emergency Call, All Call, Unit-to-Unit Voice Call, Encryption, Emergency Alarm, Call Alert, Radio Check, Radio Unit Inhibit/Uninhibit, Message Update, Status Update, Status Query, and Radio Unit Monitor.

Unsupported or Failed Test Cases

1. Call Alert, Radio Check, All Call, Radio Unit Inhibit/Uninhibit, Status Query, and Radio Unit Monitor are unsupported.
2. For Message Update only the *SU 1 to DMC Message Update* test case is supported, and for Status Update only the *Status Update from SU 1 to DMC* test case is supported.
3. Test Cases not verified for rule of three due to operational limitations of the representative equipment used for interoperability testing –
Supported test cases for Message Update

Optional Product Capabilities Required to Pass Test Cases

1. In order to pass the supported Encryption test case, a subscriber with the AES-256 Encryption capability is required.
2. In order to pass the supported Status Update and Message Update test cases, a subscriber with the P25 Data software option is required.

Project 25 Compliance Assessment Program
SDOC – L3HARRIS – XL-95P
October 25, 2022

TRUNKED SUBSCRIBER UNIT INTEROPERABILITY – FDMA

The Subscriber product has been tested for Trunked Interoperability - FDMA. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP FDMA Trunked Interoperability Testing Coverage

Full Registration, Group Voice Call, Unit to Unit Voice Call, Broadcast Voice Call, Affiliation, Announcement Group Call, Emergency Alarm, Emergency Group Call, Encryption, Intra-Location Registration Area Roaming, Deregistration, System Call, Call Alert, Short Message, Status Query, Status Update, Radio Unit Monitoring, Radio Unit Disable/Re-Enable, and Radio Check.

Unsupported or Failed Test Cases

1. Unit-to-unit call queued with target availability check – traffic channel assignment before target availability check, and Status Query are not supported.
2. Test Cases not verified for rule of three due to operational limitations of the base station or infrastructure equipment used for interoperability testing –
 - In Home Operational Mode: Unit-to-Unit Call without Target Availability Check, Unit-to-Unit Call Queued without Target Availability Check, Short Message, System Call, Radio Unit Monitoring, Radio Unit Disable/Re-Enable and Radio Check.
 - In Inter-System Roaming Operational Mode: Unverified Registration, Group Voice Call, Unit-to-Unit Call, Broadcast Voice Call, Affiliation, Announcement Group Call, Emergency Call, Encryption, System Call, Call Alert, Short Message, Status Update, Radio Unit Monitoring, Radio Unit Disable/Re-Enable and Radio Check.
3. Inter-WACN Roaming Operational Mode not verified for rule of three due to operational limitations of the base station or infrastructure equipment used for interoperability testing.

Optional Product Capabilities Required to Pass Test Cases

1. In order to pass the FDMA trunked test cases, a subscriber with the P25 Trunking capability is required.
2. In order to pass the Encryption test case, a subscriber with the AES-256 Encryption capability is required.
3. In order to pass the supported Status Update and Short Message test cases, a subscriber with the P25 Data software option is required.

TRUNKED SUBSCRIBER UNIT INTEROPERABILITY – TDMA

The Subscriber product has been tested for Trunked Interoperability - TDMA. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP TDMA Trunked Interoperability Testing Coverage

Registration, Group Voice Call, Unit-to-Unit Voice Call, Broadcast Call, Announcement Group Call, Emergency Group Call, Encryption Group Call, System Call, Radio Unit Monitoring, and Transmitting Subscriber Forced Preemption.

Project 25 Compliance Assessment Program
SDOC – L3HARRIS – XL-95P
October 25, 2022

Unsupported or Failed Test Cases

1. Unit-to-unit call queued with target availability check – traffic channel assignment before target availability check, and Transmitting Subscriber Forced Preemption test case 1: TDMA SU Forced Audio Preemption are not supported.
2. Home Operational Mode test cases not verified for rule of three due to operational limitations of the base station or infrastructure equipment used for interoperability testing –
Group Call Interrupt, Unit-to-Unit Call, System Call, Radio Unit Monitoring.
3. Inter-System and Inter-WACN Roaming Operational Modes were not verified for rule of three due to operational limitations of the base station or infrastructure equipment used for interoperability testing.

Optional Product Capabilities Required to Pass Test Cases

1. In order to pass the TDMA trunked test cases, a subscriber with the P25 Trunking and P25 Phase 2 TDMA capability is required.
2. In order to pass the supported Encryption test case, a subscriber with the AES-256 Encryption capability is required.

**Project 25 Compliance Assessment Program
SDOC – L3HARRIS – XL-95P
October 25, 2022**

SIGNATURE AND DATE

October 19, 2022

Date Signed



Vendor's Authorized Representative Signature

David Prather

Vendor's Authorized Representative Printed Name

DISCLAIMER

The information contained herein has been provided by the supplier of the product with permission to make the information publicly available. The U.S. Department of Homeland Security (DHS) Science and Technology Directorate (S&T) is making this information available as a public service; however, DHS S&T IS PROVIDING THE INFORMATION "AS IS." DHS S&T MAKES NO EXPRESS OR IMPLIED WARRANTIES AND SPECIFICALLY, DHS S&T MAKES NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE ACCURACY OR USE OF THIS INFORMATION. Reference to any specific commercial products, processes or services by trade name, trademark, supplier, or otherwise does not constitute an endorsement by or a recommendation from DHS S&T.

DHS Privacy Notice - P25 Compliance Assessment Program (CAP)

Authority: The information requested is collected under 6 U.S.C. §§194, 195,195a and 44 U.S.C. 3101

Purpose: The Department of Homeland Security (DHS) is requesting this information from you as a designated point of contact for a vendor/supplier participating in DHS' P25 Compliance Assessment Program (CAP). P25 CAP provides public safety agencies with evidence that equipment they purchase is tested against and compliant with standards for performance, conformance, and interoperability. The contact information provided to DHS will be used by DHS to contact the vendor/supplier. The information will also be placed on the P25 CAP website as part of an equipment vendor/supplier's profile and will be available to public safety agencies and others who view that profile.

Disclosure: Furnishing point-of-contact information and participating in P25 CAP is voluntary. However, failure to provide point of contact information may be the basis for denying a vendor/supplier participation in P25 CAP.

Routine Uses: The information will be used by and disclosed to S&T personnel for the purpose stated above. DHS follows approved routine uses described in the associated published system of records notice [DHS/ALL-002 Department of Homeland Security (DHS) Mailing and Other Lists System] and the published privacy impact assessment [DHS/ALL/PIA-006 DHS General Contact Lists], which you can find at www.dhs.gov/privacy.