SUBSCRIBER PRODUCT INFORMATION

Subscriber Info	Detail
Model Name:	TP9900-TPHN0A
Tested Software Versions:	Firmware Package: QIDUAL_baroDiag.0006
	136-174 MHz, 378-520 M Hz, 757-870 MHz, 896-941 MHz
Hardware Capabilities/Options & Software Options:	TPHB13-N000_0002,
Software Options.	P25 Conventional, P25 Trunked, P25 TDMA Trunked

Test case results and updated software versions for this model can be found in the Summary Test Report identified below.

TEST REQUIREMENTS CAB IDENTIFICATION

This product was tested according to the P25 CAP Test Requirements Compliance Assessment Bulletin (CAB) indicated by the checked box.

check one	P25 CAP Test Requirement CAB	Details
	P25-CAB-CAI_TEST_REQ-July 2017	Includes August 2016 P25 CAP Test Requirements; Adds TDMA performance and interoperability testing and trunked supplementary data testing
х	P25-CAB-CAI_TEST_REQ - October 2018	Includes all July 2017 P25 CAP Test Requirements; Adds minor updates to conventional interoperability testing due to TIA standard update

SUMMARY TEST REPORT IDENTIFIER ^L

Summary Test Report (STR) Identifier: STR - TAIT CON	IMUNICATIONS - SUBSCRIBER
--	---------------------------

CONTACT INFORMATION

Vendor Info	Details
Vendor Name:	Tait Communications Limited
Vendor Website URL :	https://www.taitradio.com/
P25 CAP Contact Name:	David Jackson
P25 CAP Contact Phone :	+64 3 357 0283
P25 CAP Contact Email:	david.jackson@taitcommunications.com

ENCRYPTION STATEMENT

This product complies with the P25 CAP Encryption Requirements CAB (P25-CAB-ENC_REQ). The checked box indicates how the product was tested.

¹ The Summary Test Report for this product is available upon request. Please send your STR request to <u>P25CAP@hq.dhs.gov</u> and please include the subscriber 'Vendor Name'.

x	X Tested with the AES 256 encryption algorithm and shall be available with AES 256 encryption at a minimum or without any encryption of any type.	
	Tested without the AES 256 encryption algorithm and shall only be available without any encryption of any type.	

CONVENTIONAL PERFORMANCE

The Subscriber product has been tested for Conventional Performance. All requirements were passed except for those requirements identified below under Unsupported or Failed Requirements.

P25 CAP Conventional Performance Testing Coverage

Receiver Tests: Reference Sensitivity, Faded Reference Sensitivity, Signal Delay Spread Capability, Adjacent Channel Rejection, Offset Adjacent Channel Rejection, Co-Channel Rejection, Spurious Response Rejection, Intermodulation Rejection, Signal Displacement Bandwidth, Late Entry Unsquelch Delay, and Receiver Throughput Delay.

<u>Transmitter Tests</u>: Unwanted Emissions (Adjacent Channel Power Ratio), Transmitter Power and Encoder Attack Time, Transmitter Throughput Delay, Frequency Deviation for C4FM, and Modulation Fidelity, Transient Frequency Behavior.

Unsupported or Failed Requirements

1. None

TRUNKING PERFORMANCE - FDMA

The Subscriber product has been tested for Trunking Performance - FDMA. All requirements were passed except for those requirements identified below under Unsupported or Failed Requirements.

P25 CAP FDMA Trunking Performance Testing Coverage

<u>Receiver Tests</u>: Reference Sensitivity, Faded Reference Sensitivity, Signal Delay Spread Capability, Adjacent Channel Rejection, Offset Adjacent Channel Rejection, Co-Channel Rejection, Spurious Response Rejection, Intermodulation Rejection, and Signal Displacement Bandwidth.

<u>Transmitter Tests</u>: Unwanted Emissions (Adjacent Channel Power Ratio), Power Attack time, Encoder Attack Time, Transmitter Throughput Delay, Frequency Deviation for C4FM, and Modulation Fidelity, Transient Frequency Behavior.

<u>Trunked Tests</u>: Trunking Control Channel Slot Times, Trunking Request Time, and Transmitter Time to Key on a Traffic Channel.

Unsupported or Failed Requirements

- 1. The following functionality was not supported by the test equipment/ representative base station repeater/ FNE tested with the subscriber under test:
 - a. Trunking Control Channel Slot Times 37.5 ms Slot- Encoder Attack Time
 - b. Trunking Control Channel Slot Times 37.5 ms Slot-RF Power Attack Time
 - c. Trunking Control Channel Slot Times -37.5 ms Slot- RF Power Turn Off Time
 - d. Trunking Request Time 37.5 ms Slot

TRUNKING PERFORMANCE - TDMA

The Subscriber product has been tested for Trunking Performance - TDMA. All requirements were passed except for those requirements identified below under Unsupported or Failed Requirements.

P25 CAP TDMA Trunking Performance Testing Coverage

<u>Receiver Tests</u>: Reference Sensitivity, Faded Reference Sensitivity, Signal Delay Spread Capability, Adjacent Channel Rejection, Offset Adjacent Channel Rejection, Co-Channel Rejection, Spurious Response Rejection, Intermodulation Rejection, and Signal Displacement Bandwidth. <u>Transmitter Tests</u>: Unwanted Emissions (Adjacent Channel Power Ratio), Frequency Deviation for H-CPM, Modulation Fidelity, Symbol Rate Accuracy, H-CPM Logical Channel Power measurements, and H-CPM Channel Time Alignment.

Unsupported or Failed Requirements

1. None

CONVENTIONAL DIRECT MODE INTEROPERABILITY

The Subscriber product has been tested for Conventional Direct Mode Interoperability. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP Direct Mode Interoperability Testing Coverage

Network Access Code (NAC) Operation, Group Voice Call, Emergency Call, Unit-to-Unit Voice Call, Encryption, Call Alert, Radio Check, Message Update, Status Update, Status Query, and Radio Unit Monitor.

Unsupported or Failed Test Cases

Radio Unit Monitor - Test Case 1- Radio Unit Monitor Initiated by SU 1- Group Call and Test Case 2
Radio Unit Monitor Initiated by SU 5 - Group Call are unsupported.

Optional Product Capabilities Required to Pass Test Cases

1. None

CONVENTIONAL REPEAT MODE INTEROPERABILITY

The Subscriber product has been tested for Conventional Repeat Mode Interoperability. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP Repeat Mode Interoperability Testing Coverage

Network Access Code (NAC) Operation, Group Voice Call, Emergency Call, Unit-to-Unit Voice Call, Encryption, Call Alert, Radio Check, Message Update, Status Update, Status Query, and Radio Unit Monitor.

Unsupported or Failed Test Cases

I. None

Optional Product Capabilities Required to Pass Test Cases

l. None

CONVENTIONAL REPEAT MODE with DISPATCH MONITORING CONSOLE INTEROPERABILITY

The Subscriber product has been tested for Conventional Repeat Mode with Dispatch Monitoring Console Interoperability. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP Repeat Mode Interoperability Testing Coverage

Group Voice Call, Emergency Call, All Call, Unit-to-Unit Voice Call, Encryption, Emergency Alarm, Call Alert, Radio Check, Radio Unit inhibit/Uninhibit, Message Update, Status Update, Status Query, and Radio Unit Monit or.

Unsupported or Failed Test Cases

- 1. Radio Unit Monitor Test Case 1- Radio Unit Monitor Initiated by DMC- Group Call is unsupported.
- 2 Emergency Call Test Case 2 Emergency Call from DMC and Message Update Test Case 1-Message Update from DMC and Test Case 2 - DMC to Group Message Update are unsupported by the representative FNE dispatch monitoring console tested with the subscribe r undertest.

Optional Product Capabilities Required to Pass Test Cases

I. None

TRUNKED SUBSCRIBER UNIT INTEROPERABILITY- FDMA

The Subscriber product has been tested for Trunked Interoperability - FDM A. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP FDMA Trunked Interoperability Testing Coverage

Full Registration, Group Voice Call, Unit to Unit Voice Call, Broadcast Voice Call, Affiliation, Announcement Group Call, Emergency Alarm, Emergency Group Call, Encryption, Intra-Location Registration Area Roaming, Deregistration, System Call, Call Alert, Short Message, Status Query, Status Update, Radio Unit Monitoring, Radio Unit Disable/ Re-Enable, and Radio Check.

Unsupported or Failed Test Cases

- I. Inter-SYS Roaming and Inter-WACN Roaming are unsupported
- Unit-to-Unit Voice Call Test Case 5 Unit-to-Unit Call without Target Availability Check and Test Case 6 - Unit-to-Unit Call Queued without Target Availability Check and Radio Unit Monitoring- Test Case 4 - Group Silent are unsupported.
- 3. Unit-to-Unit Voice Call Test Case 4- Unit-to-Unit Call Queued with Target Availability Check- Traffic Channel Assignment Before Target Availability Check, System Call - Test Case 1- System Call, and Radio Unit Monitoring- Test Case 1 - Individual Non-Silent, Test Case 2- Individual Silent and Test Case 3 - Group Non-Silent are unsupported by the representative base station repeater tested with the subscriber under test

Optional Product Capabilities Required to Pass Test Cases

I. None

TRUNKED SUBSCRIBER UNIT INTEROPERABILITY - TOMA

The Subscriber product has been tested for Trunked Interoperability - TOM A. All test cases were passed except for those test cases identified below under Unsupported or Failed Test Cases. Test cases that passed but require specific, sometimes optional, product capabilities are also identified below.

P25 CAP TOMA Trunked Interoperability Testing Coverage

Registration, Group Voice Call, Unit-to-Unit Voice Call, Broadcast Call, Announcement Group Call, Emergency Group Call, Encryption Group Call, System Call, Radio Unit Monitoring, and Transmitting Subscriber Forced Preemption.

Unsupported or Failed Test Cases

- I. Inter-SYS Roaming and Inter-WACN Roaming are unsupported
- 2. Radio Unit Monitoring- Test Case 4- Group Silent is unsupported.
- 3. Unit-t o-Unit Voice Call Test Case 4- Unit -to-Unit Call Queued with Target Availability Check- Traffic Channel Assignment Before Target Availability Check, System Call Test Case 1- System Call, and Radio Unit Monitoring- Test Case 1-Individual Non-Silent, Test Case 2 Individual Silent and Test Case 3 Group Non-Silent are unsupported by the representative base station repeater tested with the subscriber under test

SIGNATURE AND DATE

9 April 2024

Date Signed

I White

Vendor 's Authorized Representative Signature

Linda White

Vendor's Authorized Representative Printed Name

DISCLAIMER

The information contained herein has been provided by the supplier of the product with permission to make the information publicly available. The U.S. Department of Homeland Security (DHS) Science and Technology Directorate (S&T) is making this information available as a public service; however, DHS S&T IS PROVIDING THE INFORMATION "AS IS." DHS S&T MAKES NO EXPRESS OR IMPLIED WARRANTIES AND SPECIFICALLY, DHS S&T MAKES NO WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE ACCURACY OR USE OF THIS INFORMATION. Reference to anyspecific commercial products, processes or services by trade name, trademark, supplier, or otherwise does not constitute an endorsement by or a recommendation from DHS S&T.

DHS Privacy Notice - P25 Compliance Assessment Program (CAP)

Authority: The information requested is collected under 6 U.S.C. §§194, 195,195a and 44 U.S.C. 3101

Purpose: The Department of Homeland Security (DHS) is requesting this information from you as a designated point of contact for a vendor/supplier participating in DHS' P25 Compliance Assessment Program (CAP). P25 CAP provides public safety agencies with evidence that equipment they purchase is tested against and compliant with standards for performance, conformance, and interoperability. The contact information provided to DHS will be used by DHS to contact the vendor/supplier. The information will also be placed on the P25 CAP website as part of an equipment vendor/supplier's profile and will be available to public safety agencies and others who view that profile. **Disclosure:** Furnishing point-of-contact information and participating in P25 CAP is voluntary. However, failure to provide point of contact information may be the basis for denying a vendor/supplier participation in P25 CAP.

Routine Uses: The information will be used by and disclosed to S&T personnel for the purpose stated above. DHS follows approved routine uses described in the associated published system of records notice [DHS/ALL-002 Department of Homeland Security (DHS) Mailing and Other Lists System] and the published privacy impact assessment [DHS/ALL/PIA-006 DHS General Contact Lists], which you can find at <u>www.dhs.gov/privacy</u>.